## CITY OF LUDLOW SIDEWALK REPAIR APPLICATION (Resolution 2002-19)

DATE:				
PROPERTY ADDRESS:			CITY USE ONLY:	
<b>Must be Owner of Property</b>			Refund: Approved / Denied	
	• •			
	(Please Print)	<u> </u>	Authorization Date	
			Trumonzation Bate	
ADDRESS:			Amount to be refunded: \$	
			Thirduit to be refunded: \$\psi\$	
TELEPHON	IE NUMBER: ( <u>)</u> -	Daytii	me	
		Evoni	na	
	( ) -	Eveiii	ng	
NUMBER C	OF FEET TO BE REPLACED:		TOTAL COST: \$	
up to 20% of	NT: That the City of Ludlow will mage the total cost, not to exceed \$200.00 of sidewalks under the following term	(Two Hu		
A.	The property must be located in the	e city of L	udlow limits.	
B.	The property owner, or his designee, must make the application to the City.			
C.		et the sides	walk to be repaired and to deem whether	
D.	the repairs are necessary.  Only sidewalks adjacent to the stre	et will be	considered for the matching funds	
D.	Only sidewalks adjacent to the street will be considered for the matching funds program.			
E.	The property owner is responsible		cting the repairs and seeing that the ontractor must provide a copy of his	
F.	The property owner may elect to do the work themselves, however, payment will			
	relate to materials only in such work. (Receipts required).			
G.	A final inspection must be done by the building inspector to assure that proper			
	building code restrictions and city i	-		
H.	The City of Ludlow is exempt from	n any liabi	ility regarding such repairs.	
I have read t	he above and understand all requirem	ents per th	nis agreement.	
	SIGNATURE		DATE	

PLEASE READ THE CONCRETE SPECIFICATIONS LISTED ON PAGE 2.

## SIDEWALK, DRIVEWAY, PATIO, AND OTHER EXTERIOR CONCRETE SPECIFICATIONS

The City of Ludlow guidelines for sidewalks require that all sidewalks be a minimum of 4 inches in thickness and driveway aprons be 6 inches. The balance of the driveway must be a minimum of 4 inches.

The Kentucky Building Code requires that exterior flatwork be a minimum 3,500 p.s.i. and be air-entrained. All weather types of pours must meet minimum standards.

The City of Ludlow requires cold weather protection for any concrete poured when temperatures are 28° or below.

Excavations must be level and free of loose debris. If the ground is loose, it must be compacted. Frames shall be clean and straight. All concrete materials, forms, fillers, and the ground shall be free from frost.

Concrete (other than high-early-strength) shall be maintained above 50° F, and in a moist condition for at least the first three days after placement, unless accelerated curing methods are used as prescribed in ACI 318.

Control, expansion, and construction joints shall be used per the requirements in the KBC. Expansion joints must be placed between old work and new work.

The entire excavation shall be protected in a manner to alert the public that a danger exists.

THE BUILDING INSPECTOR MUST BE NOTIFIED <u>BEFORE</u> THE CONCRETE IS PLACED. ANY CONCRETE THAT HAS NOT HAD AN EXCAVATION INSPECTION WILL NOT BE APPROVED.

A SECOND INSPECTION IS REQUIRED AFTER THE COMPLETION OF THE JOB.

## (TO BE COMPLETED BY BUILDING INSPECTOR)

## **SIDEWALK INSPECTION REPORT**

ADDRESS:	
Date of site inspection:	
Conditions of site:	
Date of first inspection:	PASSED / FAILED*
Date of second inspection:	PASSED / FAILED**
*REASON FOR FAILING FIRST INSPECTION: _	
**DE A GON FOD FAH ING GEGOND INGDECTIO	N.T.
**REASON FOR FAILING SECOND INSPECTIO	N:
INSPECTED BY:	
Signature	Title

After a recent inspection of your sidewalk it was determined that you did not meet the requirements as outlined in the City of Ludlow's Sidewalk Repair Refund Application Form.
Application requirements that were not met are:
Because of these deficiencies, your application for refund monies is denied. If you have any questions concerning this action please do not hesitate to contact me at the office Monday through Friday at (859) 491-1233.
Sincerely,
Joe Schutzman Building and Zoning Administrator